

ADAM-5000/ECAT

4-Port Distributed High Speed I/O System for EtherCAT



RoHS
COMPLIANT
2002/95/EC

CE FCC

Features

- 32-bit ARM RISC Processor
- 4 slots with various digital and analog I/O modules is just a single EtherCAT node on the network.
- Supports EtherCAT Distributed Clock (DC) mode and SyncManager mode
- Supports the Modular Device Profile (MDP) when all modules are a pure I/O function
- Configure I/O module parameters and upgrade via a utility
- Node addresses can be fixed by rotary switches, or set by software.
- Compatible with Advantech Common Motion SDK or other EtherCAT master through ENI file generation
- 8-bit DIP switch for Mode setting and three rotate switch for up to 4,096 slave IDs (x1, x10, x100)

* I/O modules are optional

Introduction

The ADAM-5000/ECAT 4-slot distributed flexible system can provide high-speed, high-precision remote I/O for EtherCAT. It is the link between the EtherCAT automation control network and the EtherCAT I/O modules ranging from basic DI/O's to high-speed AI/O models for different application scenarios. All our EtherCAT devices have been designed and tested to meet Advantech's stringent requirements on noise immunity. Fast, accurate, highly-efficient data transmission and easy remote configuration make ADAM-5000/ECAT the perfect match in industrial automation architecture.

Specifications

Control System

- **CPU** 32-bit ARM RISC Processor
- **I/O Slots** 4
- **Memory** Flash ROM: 64M SPI
RAM: 4G DDR3
- **LED Indicators** Power LED
System status LED
EtherCAT RUN LED
EtherCAT ERROR LED
EtherCAT Port 0 LINK LED
EtherCAT Port 1 LINK LED

Communications

- **Data Transfer Rate** Up to 100 Mbps
- **Communication Cycle Time** 100 us
- **Interface** 2 x RJ-45
- **Wiring** UTP, category 5 or greater

Power

- **Power Consumption** 2.5 W @ 24 V_{DC}
(not including I/O modules)
- **Power Input** 10 ~ 30 V_{DC}

Software

- **API** Advantech Common Motion Library
- **Windows Utility** Network setting, I/O configuration

Protection

- **I/O Module Isolation** 3.000 V_{DC}
- **LAN Communication** 1.500 V_{DC}
- **Overvoltage Protection** Yes
- **Power Reversal Protection** Yes

General

- **Certification** CE, FCC class A
- **Connectors** 1 x Screw-terminal for RS-485 (communication)
1 x DB9-M for RS-232 (internal use)
1 x Screw-terminal for power input
2 x RJ-45 for LAN
- **Dimensions (W x H x D)** 231 x 110 x 75 mm
- **Mounting** DIN-rail, wall

Environment

- **Operating Humidity** 5 ~ 95%, non-condensing
- **Operating Temperature** -10 ~ 70°C (14 ~ 158°F)
- **Storage Temperature** -25 ~ 85°C (-13 ~ 185°F)

Ordering Information

- **ADAM-5000/ECAT-AE** 4-slot EtherCAT Distributed High Speed I/O System